


# MODEL J SERIES – FRAME SIZE I

## LATCH NEEDLE SINKER TOP, SINGLE KNIT MACHINE

Available in 8 Interchangeable Diameters



### Specifications

Diameter	Model No.	No. Feeds	RPM*	Cut (needles/inch)
3 inch (7.62cm)	J0312	12	300	16-32
4 inch (10.16cm)	J0416	16	300	16-32
5 inch (12.70cm)	J0520	20	240	16-32
6 inch (15.24cm)	J0624	24	200	16-32
7 inch (17.78cm)	J0728	28	171	16-32
8 inch (20.32cm)	J0832	32	150	16-32
9 inch (22.86cm)	J0936	36	133	16-32
10 inch (25.40cm)	J1040	40	120	16-32

\*Machine RPM is dependent on yarn quality and fabric configuration.

### Machine Specifications

Height	105 in. 266.70 (cm) to the top of Side Creel Tubes
Width – Outside Diameter At Positive Storage Feeders	60 in. 152.4 (cm)
At Floor	30 in. x 31 in. (76.2 cm x 81.3 cm)
Weight	1150 pounds 512.63 (kg)
Horsepower	2.0
Drive System	Tompkins Electronic AC Motor Controller with smooth and quiet Eagle Cogbelt Drive
Standard Electrics	All models 220 volts, single or 3 phase, 50/60 hertz power (voltage range 253 to 188). If other operating voltage is required, contact Tompkins
Needle Cut	16,18,24,28
Track	Single and two track
Positive Storage Feeder System	With input and output stop motions, tensioner and knot catcher – standard on all models.
Fabric Collection – Electronic	2 roll balanced takedown system to reduce high speed vibration with precision rollup for 24 inch diameter roll.
Interchangeable Heads Rapid Change System	All diameters in the Frame Size I range of 3 through 10 inches. <b>For Example:</b> The knitting head of a 10 inch diameter machine can be easily replaced with a 3 inch diameter knitting head.
Drop gates	For easy accessibility.
Machine Speeds	Start, stop and jog, with three programmable jog speeds.
Needle Detectors	Standard on all models
Lubrication System	Uniwave Model No. 419 Mini projectile lubricator with auto flush VI system.
Safety Roll Shutoff	Standard on all models

### Creel Specifications

Side Creel	Unlimited yarn cone capacity. Complete with hard tubes, support brackets and all hardware setup for double coning. Ceramic guides at all yarn bends and entrances.
------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------

### option features

- Preset revolution counter
- Lycra feed system
- Omnidirectional warning light system – 2 color
- Lock-out switch – manual motor starting switch setup for manual lockout
- Standard range of voltages available(380,416 480 and 550)
- Upper level multi-directional single fan lint blowing system
- Multi-speed positive storage feeding system



## TOMPKINS USA

623 Oneida Street  
Syracuse, New York U.S.A. 13202  
Telephone: (315) 422-8763  
FAX: (315) 422-8762  
Website: [www.tompkinsusa.com](http://www.tompkinsusa.com)  
Email: [customerservice@tompkinsusa.com](mailto:customerservice@tompkinsusa.com)